The Radar

• • •

Meteorologist Brendan Schaper







In this lesson

- Background and History
 - What is radar?
 - How does it work?
 - Limitations and advantages
 - Advancements in radar
- Radar products and applications
 - Base (Z, V, SW) and Dual-Polarization



$$R_{\text{max}}^{4} = \frac{P_{\text{t}} G^{2} I^{2} s E_{\text{i}}(n)}{k T B_{\text{n}} F_{\text{n}}(S/N)^{2} + h} L_{\text{r}} = \text{losses in the transmitter path} L_{\text{r}} = \text{losses in the receive path} L_{\text{r}} = \text{losses in$$

To simplify the scussion, the entire vuation can be converted to log form (dB):

$$40 \log(R_{max}) = \frac{1}{2} + 2G + 20 \log(1 + s + E_1(n)) + 204 dBW Az - 10 \log(B_n) - F_n - (S/N) + L_1 - L_2 - 33 dB$$

Where:

R_{max} = max num distance in meters

P, = transm power in dBW

G = antenna ain in dB

I = wavelength of the radar a shal in meters

s = RCS of targe measured in dB or dB relative to a square make

 F_n = noise figure (n. ractor converted to dB)

S/N = minimum signal is noise ratio required by receiver process; sufficient to latect the signal in dB

First, we must derive the radar equation...



War...What Is It Good For?

- Radar began as a way to detect enemy aircraft and ships
- During World War II, operators noticed "weather noise"
- WSR-1 entered service in 1947
- Since then...


WSR-1A, WSR-3, WSR-4, WSR-57, WSR-74, WSR-88D*





^{*} In operation today.

NEXRAD Coverage Below 10,000 Feet AGL



- Radars each have a 4-letter callsign
- Nashville's radar is KOHX



How Radar Works

- Antenna dish spins 360 degrees
 and can tilt up to 19.5 degrees
- Brief pulse of energy is sent
 - Pulses used to display target distance/range from the antenna
- Radar "listens" for energy to travel back from a target





Question Time

Limitations of Radar

- Refraction of radar beam
- Curvature of Earth's surface
- "Cone of silence" and proximity to radar
- Beam spreading and storm location (more ambiguity)



Limitations of Radar

- Refraction of radar beam
- Curvature of Earth's surface
- "Cone of silence" and proximity to radar
- Beam spreading and storm location (more ambiguity)



Refraction of Radar Beam

- Refraction
 - As the radar beam propagates through the atmosphere, the top of the beam travels faster than the bottom. This causes bending or refraction of the beam.
- Causes may include:
 - Pressure
 - Temperature
 - Moisture



Causes of Radar Beam Refraction

- Pressure (main cause of refraction)
 - Decreases with height, causing beam to bend downward
- Temperature
 - Generally decreases with height, causing beam to bend upward. Higher lapse rates increase upward bending.
 - *A temperature inversion will cause the beam to bend downward.
- Moisture
 - Typically, vapor pressure decreases with height, causing beam to bend downward. A more rapid decrease in vapor pressure increases downward bending (and vice versa).
 - *Increases in vapor pressure with height will cause beam to bend upward.





Normal refraction



Beam bends **less than** normal



Beam bends **more than** normal




Beam **really bends more than** normal

Limitations of Radar

- Refraction of radar beam
- Curvature of Earth's surface
- "Cone of silence" and proximity to radar
- Beam spreading and storm location (more ambiguity)





Limitations of Radar


- Refraction of radar beam
- Curvature of Earth's surface
- "Cone of silence" and proximity to radar
- Beam spreading and storm location (more ambiguity)



Cone of Silence and Proximity to Radar

- "Cone of silence" is the area where radar is limited in its ability to scan directly overhead.
- Cone of silence radius: ~ 1 nautical mile
- Storms closer to the radar are being scanned at lower levels than storms farther away










Cone of Silence Demonstration

Question Time

Limitations of Radar


- Refraction of radar beam
- Curvature of Earth's surface
- "Cone of silence" and proximity to radar
- Beam spreading and storm location (more ambiguity)






Beam Spreading













Storm Location in relation to radar beam






Storm that is cross beam





Storm Location in relation to radar beam





Storm that is down beam



Conventional v. Dual-Pol Radar

- Conventional: standard horizontal pulse
- Detects targets, "listens" for energy to return

versus

- Dual-pol: upgrades completed in 2013
- Standard horizontal pulse plus a vertical pulse
- Hail detection, raindrop size, improved rainfall estimates, non-meteorological targets
- Detection of chaff, debris, and melting layer (CC)







Conventional radar



VS

Dual-pol radar





Radar Products

- Conventional
 - Reflectivity
 - Velocity
 - Spectrum width
- Dual-pol
 - Reflectivity
 - Velocity
 - Spectrum width

...plus

- Differential reflectivity
- Correlation coefficient
- Specific differential phase







Reflectivity - March 3, 2020



Reflectivity (Z)

- Estimated returned power converted to an equivalent value
 - Measured in dBZ
- Most commonly used/seen product
 - Helps to identify precipitation and some non-meteorological targets













Velocity (V)

- Motion of a target detected, either toward or away from the radar
 - Measured in knots (kts)
- Commonly used to detect damaging winds and tornadoes

*Need to enough targets for accurate reading







Storm-relative velocity - March 3, 2020




Storm-Relative Velocity (SRM)

- Motion of a storm subtracted out to help better identify rotation
 - Measured in knots (kts), converted to miles per hour (mph)
- Storm motion (speed and direction) can be manually adjusted in some radar software

*Need to enough targets for accurate reading









- Look for gate-to-gate winds (typically shades of red and green on velocity images)
 - Strong winds, adjacent on radar, usually indicate rotation

*Reflectivity must be co-located with velocity



Identifying Rotation





Spectrum width - March 3, 2020




Spectrum Width (SW)

- Detects order/disorder in radar velocities
 - Measured in knots (kts)
- Helps to identify turbulence/wind shear (i.e. gust fronts, center of greatest rotation)
- Higher values = turbulent
- Lower values = less turbulent





^{*}Need to enough targets for accurate reading



Differential reflectivity - March 3, 2020



Differential Reflectivity (ZDR)

- Difference in horizontal and vertical reflectivity
 - Measured in dBZ
- Near 0 dBZ: spherical targets
- > 0 dBZ: <u>horizontally-oriented</u> targets
- < 0 dBZ: <u>vertically-oriented</u> targets


*Need to enough targets for accurate reading

 $\sim 0 \text{ dBZ} > 0 \text{ dBZ} < 0 \text{ dBZ}$











Differential Reflectivity (ZDR)

- Raindrops
 - The larger the drop, the more horizontal/oblate its shape
 - Larger drops = higher ZDR
- Hail
 - Tumbles as it falls, making it appear spherical
 - ZDR values near zero
- Debris
 - Does not have preferred orientation
 - Values near or slightly below zero on ZDR

> 0 dBZ

Rain


~ 0 dBZ

Hail

< 0 dBZ








Correlation coefficient - March 3, 2020




Correlation Coefficient (CC)

- Helps to detect similarities or differences in target shapes
- <u>Higher values</u> = similar targets
 - Rain and some snow
- <u>Lower values</u> = varying targets
 - Wet ice/snow or non-meteorological targets such as debris
 - Can also help detect a melting layer

*Need to enough targets for accurate reading







Applying radar analysis to real-life scenarios

Real-life scenario Radar operator on March 3, 2020




Rules

- Select from these options:
 - Severe thunderstorm warning (60+ mph wind, quarter size hail or larger)
 - Tornado warning (potential for tornado or tornado in progress)
 - No warning (includes early cancellation)








Houston, Humphreys, Dickson - 11:12 PM to 11:54 PM










Tornado Warning

11:14 PM - Warning or no warning?






11:20 PM - Warning or no warning?



CHOOSE:

Warning

Tornado Warning



11:39 PM - Warning or no warning?



CHOOSE:




Severe Thunderstorm Warning




Tornado Warning

Results Check your work...




11:14 PM - Actual warnings





11:20 PM - Actual warnings






11:39 PM - Actual warnings




Fast Forward



Davidson, Sumner, Wilson - 12:32 AM to 1:12 AM






12:35 AM - Warning or no warning?



Warning




12:40 AM - Warning or no warning?



evere Thunderstori

Severe Thunderstorm Warning

Tornado Warning




12:52 AM - Warning or no warning?




Warning

Results Check your work...




12:35 AM - Actual warnings





12:40 AM - Actual warnings





12:52 AM - Actual warnings



More information

For more on the March 2-3, 2020 tornadoes, visit weather.gov/ohx/20200303.





Next class:

Wednesday, April 15th
Observations in 3D: METARs and Upper Air Patterns

Questions?

brendan.schaper@noaa.gov

